

## **26 TYPE & 30 TYPE BRAKE VALVES**

### **New Lubrication Requirements**

SEPTEMBER 1999

Wabtec Corporation is standardizing a new lubricant to replace two lubricants that are no longer available.

#### **New Lubricant:**

NLGI Grease Grade 2: ptfе-fortified synthetic hydrocarbon-based, Wabtec Corporation Specification M-07689-02, approved source of supply is Nye Rheolube 362F, by Nye Lubricants, Inc.

#### **26 Type Brake Valves:**

Please be advised that Number 1 Calcium Base Grease, Wabtec Corporation Specification M-07650-01, is no longer available and is being replaced with the Nye Rheolube 362F listed above. This lubricant had been specified for use on certain moving parts of the 26-Type Brake Valves. Refer to the appropriate operation and Maintenance Manual, 4208-26 series, for lubrication locations in the 26-Type Brake Valves. **Important Note:** Care must be taken to prevent any application of Nye Rheolube 3362F to the O-rings, O-ring grooves, and O-ring bearing surfaces. The existing Operation and Maintenance Information requirements for O-ring lubrication remain the same.

#### **30 Type Brake Valves:**

Please be advised that EP Grease Grade O: Lithium Base with 3% Molybdenum Disulfide Additives, Wabtec Corporation Specification M-07672-01, is also being replaced with the Nye Rheolube 362F listed above. This lubricant had been specified for use on certain moving parts of the 30-Type Brake Valves. Refer to the appropriate Operation and Maintenance Manual, 4208-30 series, for lubrication locations in the 30-Type Brake Valves. **Important Note:** Care must be taken to prevent any application of Nye Rheolube 3362F to the O-rings, O-ring grooves, and O-ring bearing surfaces. The existing Operation and Maintenance Information requirements for O-ring lubrication remain the same.

#### **Other Equipment:**

Any instance of the two lubricants used elsewhere on any Wabtec Corporation product of any occurrence of the two lubricants listed elsewhere in any Wabtec Corporation manual (such as previous service bulletin 26-17) the Nye Rheolube 362F **must be** used in their place.